


Dual NPN Small Signal Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Surface mount package ideally Suited for Automatic Insertion
- NPN

Mechanical Data

- **Package:** SOT-563
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** K4V
- **Solid point:** E1 positioning point

■Maximum Ratings (Ta=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	VCBO	V	IC=10μA,IE=0	50
Collector-Emitter Voltage	VCEO	V	IC =10mA,IB=0	45
Emitter-Base Voltage	VEBO	V	IE=10μA,IC=0	6
Collector Current -Continuous	IC	mA		100
Total Device Dissipation	PC	mW		150
Junction Temperature	Tj	°C		150
Storage Temperature	TSTG	°C		-55 to +150



BC847BV

■Electrical Characteristics (Ta=25°C unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	TYP	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	IC=10μA,IE=0	50		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	IC =10mA,IB=0	45		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	IE=10μA,IC=0	6		
Collector cut-off current	I_{CBO}	nA	VCB=30V,IB=0			15
Emitter-Base Cutoff Current	I_{EBO}	nA	VEB=5V, IC=0			100
DC current gain	h_{FE}		VCE=5V,IC=2mA	200		450
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	IC=10mA,IB=0.5mA			0.1
		V	IC=100mA,IB=5mA			0.3
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	V	IC=10mA,IB=0.5mA		0.7	
		V	IC=100mA,IB=5mA		0.9	
Base-emitter Voltage	VBE	V	VCE=5V,IC=2mA	0.58	0.66	0.7
			VCE=5V, IC=10mA			0.77
Transition frequency	Ft	MHz	VCE=5V,IC=10mA,f=100MHz	100		

■ Ordering Information (Example)

Preferred P/N	Packing Code	Unit Weight(G)	Minimum Package(Pcs)	Inner Box Quantity(Pcs)	Outer Carton Quantity(Pcs)	Delivery Mode
BC847BV	F2	Approximate 0.0035	3000	30000	120000	7" reel



■ Characteristics (Typical)

Fig. 1 - Static Characteristics




Fig. 2 - DC Current Gain Characteristics




Fig. 3 - Collector-Emitter Saturation Voltage Characteristics




Fig. 4 - Base-Emitter Saturation Voltage Characteristics




Fig. 5 - Base-Emitter Voltage Characteristics








Fig. 6 - Collector Power Derating Curve






■ Outline Dimensions

SOT-563



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.006	0.011	0.150	0.300
B	0.043	0.051	1.100	1.300
C	0.059	0.067	1.500	1.700
D	0.016	0.024	0.400	0.600
G	0.035	0.043	0.900	1.100
H	0.059	0.067	1.500	1.700
K	0.021	0.026	0.550	0.650
L	0.004	0.011	0.100	0.300
M	0.004	0.007	0.100	0.180

■ Suggested Pad Layout



单位: mm

SUGGESTED SOLDER PAD LAYOUT



BC847BV

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.