




MDS35-4 THRU MDS35-16

Three Phase Bridge Rectifiers



Features

- UL recognition, file #E230084
- Glass passivated chip
- High surge current capability
- Low thermal resistance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** MDS35
Molding compound meets UL 94 V-0 flammability rating,
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102

■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MDS35-4	MDS35-6	MDS35-8	MDS35-10	MDS35-12	MDS35-14	MDS35-16	
Device marking code			MDS35-4	MDS35-6	MDS35-8	MDS35-10	MDS35-12	MDS35-14	MDS35-16	
Repetitive Peak Reverse Voltage	V _{RRM}	V	400	600	800	1000	1200	1400	1600	
Average Rectified Output Current @60Hz sine wave, R-load, With heatsink T _c =85°C	I _O	A	35							
Surge(Non-repetitive)Forward Current @60HZ Half- sine Wave, 1 cycle, T _a =25°C	I _{FSM}	A	400							
Current Squared Time @1ms≤t<8.3ms T _j =25°C, Rating of per diode	I ² t	A ² S	660							
Storage Temperature	T _{stg}	°C	-55~+150							
Junction Temperature	T _j	°C	-55~+150							
Dielectric Strength, Terminals to case, AC 1 minute	V _{dis}	KV	2.5							
Mounting Torque	TOR	kg·cm	10							

■Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MDS35-4	MDS35-6	MDS35-8	MDS35-10	MDS35-12	MDS35-14	MDS35-16
Maximum instantaneous forward voltage drop per diode	V _{FM}	V	I _{FM} =25A	1.2						
Maximum DC reverse current at rated DC blocking voltage per diode	I _{RRM}	μA	V _{RM} =V _{RRM}	10						

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MDS35-4	MDS35-6	MDS35-8	MDS35-10	MDS35-12	MDS35-14	MDS35-16
Thermal Resistance Between junction and case, With heatsink	R _{θ J-C}	°C/W	0.85						



MDS35-4 THRU MDS35-16

Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MDS35-4~MDS35-16	A1	Approximate 17.5	50	50	500	Paper Box

Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3:Instantaneous Forward Voltage






FIG4:Typical Reverse Characteristics





MDS35-4 THRU MDS35-16

■ Outline Dimensions



MDS35		
Dim	Min	Max
A	32	33
B	23.7	24.7
C	15.5	16.5
D	8.6	9.4
E	22	24
F	6.2	6.5
G	4.8	5.4
H	0.75	0.85



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.