



Surface Mount Ultrafast Rectifier Diode



Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Solder dip 260 °C max. 10 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

Mechanical Data

- **Package:** TO-277
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes the cathode end

■ Maximum Ratings ($T_j=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR10U60
Device marking code			MUR10U60
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	600
Maximum RMS Voltage	V_{RMS}	V	420
Maximum DC blocking Voltage	V_{DC}	V	600
Average Rectified Output Current @60Hz sine wave, Resistance load, T_c (FIG.1)	I_o	A	10.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, $T_j=25^\circ\text{C}$	I_{FSM}	A	180
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, $T_j=25^\circ\text{C}$			360
Current squared time @1ms $\leq t \leq$ 8.3ms $T_j=25^\circ\text{C}$	I^2t	A ² s	134
Typical Junction capacitance @4V, 1MHz	C_j	pF	63
Storage Temperature	T_{stg}	°C	-55 ~ +150
Junction Temperature	T_j	°C	-55 ~ +150



MUR10U60

■ Electrical Characteristics (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Instantaneous forward voltage drop per diode	V _{FM}	V	T _j =25°C	I _{FM} =10.0A	-	1.25	1.70
			T _j =125°C		-	1.05-	1.50
Reverse Recovery Time	T _{RR}	ns	T _j =25°C	I _F =0.5A, I _R =1.0A, I _{rr} =0.25A	-	38	50
DC reverse current at rated DC blocking voltage per diode	I _{RRM1}	uA	T _j =25°C	V _{RM} =V _{RRM}	-	-	5
	I _{RRM2}		T _j =125°C		-	-	200

■ Thermal Characteristics (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR10U60
Thermal resistance	R _{θJA} ⁽¹⁾	°C/W	100
	R _{θJC} ⁽¹⁾		25

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR10U60	F1	Approximate 0.0821	5000	/	80000	13" reel

■ Characteristics (Typical)

FIG.1: I_o-T_c Curve





FIG.2: Forward Surge Current Capability





MUR10U60

FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics



■ Outline Dimensions




TO-277		
Dim	Min(mm)	Max(mm)
A	3.90	4.10
B	1.70	1.90
C	6.40	6.60
D	5.30	5.50
E	0.80	1.00
F	1.85 ref.	
G	0.35	0.45
H	1.10	1.20
I	4.10	4.50
J	1.50	1.90
K	2.90	3.40
L	0.55	0.75
M	0.50 ref.	
N	1.15 ref.	



MUR10U60

■ Suggested pad layout



DIM	MIN.(mm)
A	3.36
B	4.86
C	0.85
P	1.84
Q1	1.40
Q2	1.40



MUR10U60

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.