




N-Channel Enhancement Mode Field Effect Transistor



DFN3.3X3.3



Product Summary

- V_{DS} 60V
- I_D 53A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) < 8.2 mohm
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) < 12 mohm
- 100% UIS Tested
- 100% ∇V_{DS} Tested

General Description

- Split Gate Trench MOSFET technology
- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$

Applications

- DC-DC Converters
- Power management functions
- Industrial and Motor Drive application

■ Absolute Maximum Ratings ($T_A=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-source Voltage	V_{DS}	60	V
Gate-source Voltage	V_{GS}	± 20	V
Drain Current	I_D	$T_C=25^\circ C$	53
		$T_C=100^\circ C$	34
Pulsed Drain Current ^A	I_{DM}	162	A
Avalanche energy ^B	E_{AS}	195	mJ
Total Power Dissipation	P_D	$T_C=25^\circ C$	45
		$T_C=100^\circ C$	18
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	2.8	$^\circ C/W$
Junction and Storage Temperature Range	T_J, T_{STG}	-55~+150	$^\circ C$

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJQ53G06A	F1	Q35G06	5000	10000	100000	13" reel



YJQ53G06A

■ Electrical Characteristics (T_J=25°C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} = 0V, I _D =250μA	60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V	T _J =25°C		1	μA
			T _J =55°C		5	
Gate-Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA	1.2	1.7	2.5	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D =20A		7.2	8.2	mΩ
		V _{GS} = 4.5V, I _D =10A		9.1	12	
Diode Forward Voltage	V _{SD}	I _S =20A, V _{GS} =0V		0.8	1.2	V
Maximum Body-Diode Continuous Current	I _S				53	A
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =30V, V _{GS} =0V, f=1MHZ		1980		pF
Output Capacitance	C _{oss}			470		
Reverse Transfer Capacitance	C _{rss}			14		
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =10V, V _{DS} =30V, I _D =20A		31		nC
Gate-Source Charge	Q _{gs}			6		
Gate-Drain Charge	Q _{gd}			5		
Reverse Recovery Chrage	Q _{rr}	I _F =20A, di/dt=500A/us		17		ns
Reverse Recovery Time	t _{rr}			58		
Turn-on Delay Time	t _{D(on)}	V _{GS} =10V, V _{DD} =30V, R _L =2.5Ω R _{GEN} =3Ω		10		ns
Turn-on Rise Time	t _r			5		
Turn-off Delay Time	t _{D(off)}			30		
Turn-off fall Time	t _f			8		

A. Pulse Test: Pulse Width ≤ 300us, Duty cycle ≤ 2%.

B. T_J=25°C, V_{DS}=55V V_{DD}=40 V_{GS}=10 L=1mH



■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance



YJQ53G06A




Figure7. Safe Operation Area







Figure8. Switching wave

■ DFN3.3X3.3 Package information



A	B	C	C1
3.25±0.05	3.25±0.05	0.8±0.05	0.2±0.02
C2	D	E	F
0.05Max	1.9±0.1	2.35±0.15	0.45±0.05
G	H	e	
0.3±0.05	0.35±0.05	0.65±0.05	
单位: mm			





YJQ53G06A

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.